





















オフィス / ホテルに

乗用

<p>1 P1150A - CO 積載：1,150kg 定員：17人</p> 	<p>2 P1350A - CO 積載：1,350kg 定員：20人</p> 	<p>3 P1350B - CO 積載：1,350kg 定員：20人</p> 
<p>4 P1600B - CO 積載：1,600kg 定員：24人</p> 	<p>5 P1600A - CO 積載：1,600kg 定員：24人</p> 	<p>6 P1600C - CO 積載：1,600kg 定員：24人</p> 
<p>7 P1600D - CO 積載：1,600kg 定員：24人</p> 	<p>8 P1800X1 - CO 積載：1,800kg 定員：27人</p> 	<p>9 P1800X2 - CO 積載：1,800kg 定員：27人</p> 
<p>10 P2000X2 - CO 積載：2,000kg 定員：30人</p> 	<p>11 P2000X3 - CO 積載：2,000kg 定員：30人</p> 	 <p>大阪産業創造館</p>

機種名	昇降路有効内法	間口	奥行	前後扉
1 P1150A - CO		2400	2250	-
2 P1350A - CO		2400	2450	-
3 P1350B - CO		2500	2350	-
4 P1600B - CO		2500	2550	-
5 P1600A - CO		2600	2500	-
6 P1600C - CO		2700	2400	-
7 P1600D - CO		2750	2350	-
8 P1800X1 - CO		2600	2690	-
9 P1800X2 - CO		2700	2590	-
10 P2000X2 - CO		2600	2840	-
11 P2000X3 - CO		2700	2740	-

人荷共用

<p>1 S1150X1 - 2S 積載：1,150kg 定員：17人</p> 	<p>2 S1150X2 - 2S 積載：1,150kg 定員：17人</p> 	<p>3 S1200X1 - 2S 積載：1,200kg 定員：18人</p> 	<p>4 S1300X1 - 2S 積載：1,300kg 定員：20人</p> 	<p>5 S1350X1 - 2S 積載：1,350kg 定員：20人</p> 
<p>6 S1450X1 - 2S 積載：1,450kg 定員：22人</p> 	<p>7 S1600X1 - 2S 積載：1,600kg 定員：24人</p> 	<p>8 S1600X2 - 2S 積載：1,600kg 定員：24人</p> 	<p>9 S1700X1 - CO 積載：1,700kg 定員：26人</p> 	<p>10 S1700X1 - 4C 積載：1,700kg 定員：26人</p> 
<p>11 S1800X1 - CO 積載：1,800kg 定員：27人</p> 	<p>12 S1800X1 - 4C 積載：1,800kg 定員：27人</p> 	<p>13 S1800X2 - CO 積載：1,800kg 定員：27人</p> 	<p>14 S1800X2 - 4C 積載：1,800kg 定員：27人</p> 	<p>15 S2000X1 - CO 積載：2,000kg 定員：30人</p> 
<p>16 S2000X1 - 4C 積載：2,000kg 定員：30人</p> 	<p>17 S2000X2 - CO 積載：2,000kg 定員：30人</p> 	<p>18 S2000X2 - 4C 積載：2,000kg 定員：30人</p> 	<p>19 S2000X3 - CO 積載：2,000kg 定員：30人</p> 	<p>20 S2000X3 - 4C 積載：2,000kg 定員：30人</p> 

機種名	昇降路有効内法	間口	奥行	前後扉時奥行
1 S1150X1 - 2S		2300	2490	2680
2 S1150X2 - 2S		2400	2440	-
3 S1200X1 - 2S		2400	2440	2630
4 S1300X1 - 2S		2500	2440	2630
5 S1350X1 - 2S		2600	2440	-
6 S1450X1 - 2S		2600	2440	2630
7 S1600X1 - 2S		2600	2590	2780
8 S1600X2 - 2S		2700	2490	2680
9 S1700X1 - CO		2550	2790	-
10 S1700X1 - 4C		2550	2855	-

機種名	昇降路有効内法	間口	奥行	前後扉
11 S1800X1 - CO		2600	2690	-
12 S1800X1 - 4C		2600	2755	-
13 S1800X2 - CO		2700	2590	-
14 S1800X2 - 4C		2700	2655	-
15 S2000X1 - CO		2550	3090	-
16 S2000X1 - 4C		2550	3155	-
17 S2000X2 - CO		2600	2840	-
18 S2000X2 - 4C		2600	2905	-
19 S2000X3 - CO		2700	2740	-
20 S2000X3 - 4C		2700	2805	-